



awilux

AMAZING LIFE QUALITY



Aluminum windows
and sliding systems

Awilux Poland – we act with passion

Awilux Polska is a team of qualified specialists who create every day, with technical precision, window, and door constructions to meet the expectations of our customers. A wide range of technological solutions and a rich color palette means that windows can be adapted to any aesthetic environment and give the building the right character. Our goal is to promote solutions aimed at increasing safety and energy efficiency.

We have been operating on the market since 2006, basing our production on German SCHÜCO technology. This means solidity, rigorous adherence to the highest technical standards, and precision of execution. We attach great importance to timeliness and efficient execution of orders. This is ensured by our modern production lines and experienced staff. We are successfully building a network of showrooms on the Polish market. All our partners take part in training on SCHÜCO systems and modern assembly techniques. Our aim is to remain an important and reliable partner in the implementation of your plans and investments for many years to come.

We will meet even the most complex projects.



The luxury of modern architecture

Timeless elegance is a combination of modernity with design and innovation. Aluminum windows and sliding systems have become a permanent feature of architectural trends. They are eagerly chosen by people who value modern style and open space.

More and more advanced production technologies and high-quality components allow us to meet the highest expectations regarding energy efficiency or passivity of the building. We want the house to harmonize with our personality, to match our lifestyle, to be simply comfortable.

Until recently investors were afraid that large windows would cause serious heat losses. Today joinery manufacturers give a clear answer: Absolutely not!

Sunlight is an invaluable source of energy and well-being. Aluminum sliding doors are the ideal solution for getting light into your interior. The exceptional stability of aluminum makes it possible to create constructions with narrow profiles and extremely large glazing for a perfect view and maximum light. The impressive, large-scale glazing gives the interiors and the building façade a timeless elegance.



WINDOWS

ALUMINUM

SCHÜCO

Premium Partner



Schüco AWS 90.SI+

Schüco AWS 90. SI+ aluminum windows offer excellent thermal insulation. They meet all architectural requirements in terms of design and possibilities of shaping the appearance of the building.

The installation depth is only 90 mm. This is an excellent choice for those who appreciate the use of additional energy potential in the home thanks to the modern fitting system. Thoughtful design with thermal foam dividers improves the thermal parameters of the window. The AWS 90. SI+ window system is fully compatible with external roller blinds and mosquito nets offered by us.

- Maximum thermal protection with profile installation depth of 90 mm: U_f value = $1,0 \text{ W/m}^2\text{K}$ (width of visible profiles is 117 mm),
- Specialized seal,
- Optimized insulation zone with foam thermal break,
- Wide range of profiles for different solutions, passive building level: new standard for thermal insulation of aluminum windows,
- High quality fittings guarantee comfort and safety for years.

$$U_w = 0,8 \text{ W/m}^2\text{K}^*$$

$$US = 0.14 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 1230 mm*1480 mm with glazing package $U_g = 0,5$, Ψ (psi) = $0,056 \text{ W/m}^2\text{K}$
**Uw-Value is based on the ISO/Passive House thermal performance rating program.



Schüco AWS 75.HI

The Schüco AWS 75.HI window system with an installation depth of 75 mm combines good thermal insulation with the unique advantages of aluminum: durability, strength, narrow visible profile width and rich design.

The broad range of products enables outward opening windows, balcony doors with low threshold and many other design requirements to be realized. Construction possibilities allow to create a very large tilt and turn window. In all cases we have the possibility to fit external roller blinds and mosquito nets offered by Awilux.

- Improved thermal insulation, 75 mm depth: Uf value from 1.6 W/m² (visible profile width 117 mm)
- Available with outward opening sash or as a tilt and turn window,
- Window system perfectly suited for both new buildings and those undergoing renovation,
- Compatible with Schüco door range,
- The system is available in a wide range of RAL colors.

$$U_w = 0,88 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.15 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 1230 mm*1480 mm with glazing package Ug = 0.5, Ψ (psi) = 0.056 W/m²K

**Uw-Value is based on the ISO/Passive House thermal performance rating program.



ALUMINUM SLIDING SYSTEMS

SCHÜCO
Premium Partner

Modern homes integrate indoor and outdoor spaces. Architects design rooms that are open and combine many functions. At the design stage, we make sure that our house blends in with the surrounding landscape. This is important for people who want to be closer to what is visible outside the window. The lack of rigid divisions of space gives us the feeling that we are part of the world around us.

Aluminum sliding systems fill the interior of the house with light, giving the architecture of the building an individual character. They enable the best use of the available functional space. They create a spacious interior of the highest standard. Despite their large dimensions their operation is exceptionally simple and convenient.



Schüco ASS 77 PD

architecture saturated with light

Architecture without limits. This is what you can say about the ASS 77 PD sliding door. The system offers the possibility of glazing, guaranteeing a beautiful view and almost invisible frames in the interior.

A solution for connoisseurs of space and freedom of living!

- Maximum transparency and greatest possible light penetration thanks to minimum profile widths from 30 mm in the middle section,
- The possibility of using different glazing even up to 60 mm thick,
- The completely flat frame with concealed integrated door profile gives the system an extraordinary connection to the floor and no threshold
- The automatic drive and locking system allows you to enjoy operating convenience,
- Fast, quiet and convenient opening and closing with a push button via an external control panel,
- Ideal system for large glazing - innovative solution of running rails with load bearing capacity up to 500 kg,
- Security enhancing solution - burglary protection up to and including RC2 (WK2) class.

$$U_w = 1,1 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.19 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 3500 mm*2300 mm with glazing package $U_g = 0,5$, Ψ (psi) = 0,056 $\text{W/m}^2\text{K}$.

**Uw-Value is based on the ISO/Passive House thermal performance rating program.



reddot design award
best of the best 2012



reddot award 2018
winner

Schüco ASS 77 PD sliding system has won many design awards, such as: "iF Design Award 2018" and "Red Dot Award 2018" for Seamless Combination, the perfect combination of sliding and façade system with panoramic design and the "iF Product Design Award 2012" or, for example, the "Red Dot Design Award best of the best 2012"

Schüco ASE 80.HI

Lift&Slide doors

The almost noiseless and easy to operate system provides easy access to balconies, terraces and conservatories. All sliding elements move in parallel. Rooms become more spacious, elegant and functional.

The Schüco ASE 80. HI Lift&Slide system combines the advantages of aluminum with future-proof thermal insulation in the passive house standard to create sustainable architecture. In this generation, increased sash weight and larger formats go hand in hand with design and comfort that are not mutually exclusive.

- Aluminum profiles with high thermal insulation and high stability,
- Maximally narrowed profiles - the central mullion and the sash profile are only 40 mm thick,
- Large-size sashes up to 3.5x3.2 m or 3.2x3.5 m create spacious interiors filled with light, possibility to use anti-burglary hardware,
- Excellent watertightness,
- Ideal soundproofing of rooms.

$$U_w = 0,9 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.16 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 3500 mm*2300 mm with glazing package $U_g = 0,5$, Ψ (psi) = 0,056 W/m²K.

**Uw-Value is based on the ISO/Passive House thermal performance rating program.



Schüco ASS 70 FD

folding sliding door (accordion)

The warm folding-sliding door allows the glazed partition to be opened almost completely. The individual door elements fold up like an accordion quickly and compactly into narrow packages, taking up little space.

The door sashes can be simply and easily opened inwards or outwards and can be slid to the right and/or left. Schüco aluminum folding-sliding doors are the perfect way to enlarge your interior and connect it with its surroundings.

- Sturdy, thermally insulated aluminum profiles,
- Opportunity for additional noise protection enhancement,
- Low threshold option,
- Possibility to use different colors of profiles on the inside and outside,
- Use in residential and public buildings.

$$U_w = 1,3 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.23 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 3500 mm*2300 mm with glazing package $U_g = 0,5$, Ψ (psi) = $0,062 \text{ W/m}^2\text{K}$,

**Uw-Value is based on the ISO/Passive House thermal performance rating program.



WINDOWS

ALUMINUM

aliplast
aluminium systems



Aiplast Star

- Installation depth 90 mm,
- Modern aluminum system for designing windows and doors requiring very good thermal insulation,
- Thermal break with a depth of 45 mm provides a reliable thermal barrier,
- Innovative system of draining water from the structure (no visible elements to cover drainage holes),
- Wide selection of colors according to RAL palette, wood imitation colors, anodized.

$$U_w = 0,8 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.14 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 1230 mm*1480 mm with glazing package $U_g = 0,5$, Ψ (psi) = 0,045 W/m²K.
**Uw-Value is based on the ISO/Passive House thermal performance rating program.



Aiplast Imperial

- Installation depth: 65 mm,
- Imperial system with increased thermal insulation, designed for constructing windows, doors and showcases, special thermal inserts inserted between thermal breaks and around the glass,
- The system is designed for use in residential and public buildings, the system allows modern window construction solutions to be designed in many variants,
- Innovative system of draining water from the construction (no visible elements blocking the drainage holes),
- Wide selection of colors according to RAL palette, wood-like colors, anode.

$$U_w = 1,2 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.21 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 1230 mm*1480 mm with glazing package $U_g = 0,5$, Ψ (psi) = 0,045 W/m²K.
**Uw-Value is based on the ISO/Passive House thermal performance rating program.

Aliplast Genesis

- Installation depth 75 mm,
- A three-chamber window system intended for constructing windows with increased thermal insulation properties, both in public utility buildings and in single- and multi-family housing,
- The system uses modern insulation materials, which are currently new on the market. Apart from the classic central window seal, an additional thermal seal has been designed. Thanks to this solution very high window tightness (air infiltration, water tightness) and innovative look and aesthetics have been obtained,
- Genesis 75 window system sets a new standard of windows insulation, while maintaining the highest ergonomics and modern profiles aesthetics,
- Wide selection of colors according to RAL palette, wood-like colors, anode.

$$U_w = 0,9 \text{ W/m}^2\text{K}^*$$

$$\text{U-Factor} = 0.16 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 1230 mm*1480 mm with glazing package $U_g = 0,5$, Ψ (psi) = 0,045 W/m²K.

**U_w-Value is based on the ISO/Passive House thermal performance rating program.



Aiplast Ultraglidle

for the terrace, the veranda, the winter garden...

The modern and versatile Ultraglidle system is particularly recommended to investors who value aesthetics and high functionality. The system is very flexible. The possibility of designing large glazing allows for innovative interior lighting, while maintaining stability, lightness and functionality of the structure.

Ultraglidle sliding windows can be constructed with a low threshold, which ensures comfortable use of the structure and an elegant design. Thanks to the technology used, the threshold level is flush with the floor. An interesting solution is also the angular connection (90 degrees), dedicated to large corner glazing. It is ideal for modern apartment buildings or buildings requiring open space. After moving the sash, no vertical mullion is left. You can also use the Monorail solution, in which thanks to a special construction of the hidden frame, the glazing in the fixed element reaches the floor, while increased thermal insulation is maintained.

- Sliding system with increased thermal insulation,
- 3 or 5 sash chambers, frame width: 64 mm, frame depth: 153 mm,
- Sash width: 100 mm, sash depth: 67 mm,
- Possible combinations of two-three and four elements based on two-track system,
- Possible three-track solutions, corner solutions as an option,
- In the version with an insulated threshold and profiles it is possible to obtain a coefficient of $U_w = 1.0 \text{ W/m}^2\text{K}$,
- Ideal solution for large glazing.

$$U_w = 1,3 \text{ W/m}^2\text{K}^*$$

$$U\text{-Factor} = 0.23 \text{ BTU/hr-ft}^2\text{-}^\circ\text{F}^{**}$$

*Parameter calculated for reference window 3500 mm*2300 mm with glazing package $U_g = 0,5$, Ψ (psi) = $0,045 \text{ W/m}^2\text{K}$.

** U_w -Value is based on the ISO/Passive House thermal performance rating program.



GLAZING

SunEnergy and SunEnergy+

The **SunEnergy+** glazing package offered by Awilux Polska has excellent thermal insulation parameters, an unusually light and neutral color and exceptional transparency.

Thanks to all these parameters, householders in buildings with **SunEnergy+** glazing can enjoy perfectly lighted rooms. This is extremely important in our temperate climate. Well-lit rooms have recently become one of the leading architectural themes. There are various additional solutions that allow you to enjoy well-being and health in your own home at any time of the year. One such solution is **SunEnergy+**.

Comparison of light and energy transmission parameters

	SunEnergy+	Standard glazing	SunEnergy	Standard glazing
U_g coefficient	0,5	0,5	1,1	1,0
Package construction	4/18/4/18/4	4/16/4/16/4	4/16/4	4/16/4
Light transmittance coefficient L_T	74	57	84	71
Energy transmittance g	53	35	64	50





awilux
AMAZING LIFE QUALITY



www.awilux.com